

DVGW-Baumusterprüfzertifikat

DVGW type examination certificate

DG-4312CL0140

Registriernummer
registration number

Anwendungsbereich <i>field of application</i>	Produkte der Gasversorgung <i>products of gas supply</i>
Zertifikatinhaber <i>owner of certificate</i>	N.T.M. S.p.A. Via John Maynard Keynes, 15/17, I-25030 Brandico (BS)
Vertreiber <i>distributor</i>	N.T.M. S.p.A. Via John Maynard Keynes, 15/17, I-25030 Brandico (BS)
Produktart <i>product category</i>	gas fittings: Shut-off valve <= MOP 5 (4312)
Produktbezeichnung <i>product description</i>	straight pattern ball valve
Modell <i>model</i>	Art. 39... (ELIOS)
Prüfberichte <i>test reports</i>	type testing: V-A1407-00/10 from 29.04.2010 (TSG)
Prüfgrundlagen <i>basis of type examination</i>	DIN EN 331 (01.04.1999)

DVGW

Ablaufdatum / AZ
date of expiry / file no. 29.04.2015 / 09-0507-GNE

12.07.2010 Rie A-1/2

Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle
date, issued by, sheet, head of certification body

DVGW CERT GmbH - von der Deutschen Akkreditierungsstelle Technik (DATech)
in der TGA GmbH akkreditiert für die Konformitätsbewertung von Produkten der
Gas- und Wasserversorgung

DVGW CERT GmbH - accredited by Deutsche Akkreditierungsstelle Technik
(DATech) in the TGA GmbH for conformity assessment of products of gas and
water supply



DAT-ZE-009/96-02

DVGW CERT GmbH
Josef-Wirmer-Straße 1-3
53123 Bonn

Telefon: +49 228 91 88-888

Telefax: +49 228 91 88-993

eMail: info@dvgw-cert.com

Gasart <i>gas category</i>	Bemerkungen <i>remarks</i>
fuel gases of the 1., 2. & 3. gas family	according to DIN EN 437

Typ <i>type</i>	Technische Daten <i>technical data</i>	Bemerkungen <i>remarks</i>
3900; 3901; 3910; 3911; 3920; 3921; 3930; 3931; 3932; 3922	nominal pressure rating: MOP 5-20 nominal diameter: DN 15	
3900; 3901; 3910; 3911; 3920; 3921; 3930; 3931; 3932; 3922	nominal pressure rating: MOP 5-20 nominal diameter: DN 20	
3900; 3901; 3910; 3911; 3920; 3921; 3930; 3931; 3932; 3922	nominal pressure rating: MOP 5-20 nominal diameter: DN 25	
3900; 3901; 3910; 3911; 3930; 3931; 3932	nominal pressure rating: MOP 5-20 nominal diameter: DN 32	
3900; 3901; 3910; 3911; 3930; 3931; 3932	nominal pressure rating: MOP 5-20 nominal diameter: DN 40	
3900; 3901; 3910; 3911; 3930; 3931; 3932	nominal pressure rating: MOP 5-20 nominal diameter: DN 50	

Ausführungsvariante <i>type variation</i>	Erläuterungen <i>explanations</i>
3900	with steel-handle, connections: on both sides female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3901	with steel-handle, connections: on the input side male thread R 1/2...R 2 according to DIN EN 10226-1, on the output side female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3910	with aluminum-handle, connections: on both sides female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3911	with aluminum-handle, connections: on the input side male thread R 1/2...R 2 according to DIN EN 10226-1, on the output side female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3920	with butterfly-handle, connections: on both sides female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3921	with butterfly-handle, connections: on the input side male thread R 1/2...R 2 according to DIN EN 10226-1, on the output side female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3930	with flat steel-handle, connections: on both sides female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3931	with flat steel-handle, connections: on the input side male thread R 1/2...R 2 according to DIN EN 10226-1, on the output side female thread Rp 1/2...Rp 2 according to DIN EN 10226-1
3932	with flat steel-handle, connections: on both sides male thread R 1/2...R 2 according to DIN EN 10226-1
3922	with butterfly-handle, connections: on both sides male thread R 1/2...R 2 according to DIN EN 10226-1

zertifizierte Bauteile / Werkstoffe**certified components**

Registr.-Nr. <i>registration no.</i>	Bauteil (Produktart) <i>component</i>	Modell/Typ <i>model/type</i>	Hersteller <i>manufacturer</i>
NG-5112AT0428	Sealing material made of elastomers for F-700/F-700 gas appliances		Tecnogomma International S.p.A.
NG-5146AR0617	Sealing and jointing materials for screwed joint of gas appliances and gas plants, hardening	LOCTITE 2701/LOCTITE 2701	Henkel AG & Co. KGaA

Verwendungshinweise / Bemerkungen**hints of utilization / remarks**

ambient temperature range: -20...+60 °C

DVGW